


# SKiiP26GB12F4V1



MiniSKiiP® 2 Dual


## SKiiP26GB12F4V1

### Features

- Fast Trench 4 IGBTs
- Robust and soft freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognised: File no. E63532
- NTC T-Sensor

### Remarks

- Max. case temperature limited to  $T_C = 125^\circ\text{C}$
- Product reliability results valid for  $T_j \leq 150^\circ\text{C}$  (recommended  $T_{j,op} = -40 \dots +150^\circ\text{C}$ )



GB


### Absolute Maximum Ratings

Symbol	Conditions	Values	Unit	
<b>Inverter - IGBT</b>				
$V_{CES}$	$T_j = 25^\circ\text{C}$	1200	V	
$I_C$	$T_j = 175^\circ\text{C}$	$T_s = 25^\circ\text{C}$	202	A
		$T_s = 70^\circ\text{C}$	164	A
$I_{Cnom}$		200	A	
$I_{CRM}$	$I_{CRM} = 2 \times I_{Cnom}$	400	A	
$V_{GES}$		-20 ... 20	V	
$t_{psc}$	$V_{CC} = 800\text{ V}$	$T_j = 150^\circ\text{C}$	10	$\mu\text{s}$
	$V_{GE} \leq 15\text{ V}$			
	$V_{CES} \leq 1200\text{ V}$			
$T_j$		-40 ... 175	$^\circ\text{C}$	
<b>Inverse - Diode</b>				
$I_F$	$T_j = 175^\circ\text{C}$	$T_s = 25^\circ\text{C}$	194	A
		$T_s = 70^\circ\text{C}$	154	A
$I_{Fnom}$		200	A	
$I_{FRM}$	$I_{FRM} = 3 \times I_{Fnom}$	600	A	
$I_{FSM}$	10 ms, sin 180°, $T_j = 150^\circ\text{C}$	990	A	
$T_j$		-40 ... 175	$^\circ\text{C}$	
<b>Module</b>				
$I_{t(RMS)}$	$T_{terminal} = 80^\circ\text{C}$ , 20 A per spring	200	A	
$T_{stg}$		-40 ... 125	$^\circ\text{C}$	
$V_{isol}$	AC sinus 50 Hz, t = 1 min	2500	V	

### Characteristics

Symbol	Conditions	min.	typ.	max.	Unit
<b>Inverter - IGBT</b>					
$V_{CE(sat)}$	$I_C = 200\text{ A}$ $V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	2.05	2.40	V
		$T_j = 150^\circ\text{C}$	2.50	2.85	V
$V_{CE0}$	chipelevel	$T_j = 25^\circ\text{C}$	0.80	0.90	V
		$T_j = 150^\circ\text{C}$	0.70	0.80	V
$r_{CE}$	$V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	6.3	7.5	m $\Omega$
		$T_j = 150^\circ\text{C}$	9.0	10	m $\Omega$
$V_{GE(th)}$	$V_{GE} = V_{CE}$ , $I_C = 7.6\text{ mA}$	5.2	5.8	6.4	V
$I_{CES}$	$V_{GE} = 0\text{ V}$ $V_{CE} = 1200\text{ V}$	$T_j = 25^\circ\text{C}$	0.1	0.3	mA
			-	-	mA
$C_{ies}$	$V_{CE} = 25\text{ V}$		12.30		nF
$C_{oes}$	$V_{GE} = 0\text{ V}$				nF
$C_{res}$			0.69		nF
$Q_G$	- 8 V...+ 15 V		1130		nC
$R_{Gint}$	$T_j = 25^\circ\text{C}$		3.8		$\Omega$
$t_{d(on)}$	$V_{CC} = 600\text{ V}$ $I_C = 200\text{ A}$	$T_j = 150^\circ\text{C}$	167		ns
$t_r$	$R_{Gon} = 2\ \Omega$	$T_j = 150^\circ\text{C}$	52		ns
$E_{on}$	$R_{Goff} = 2\ \Omega$	$T_j = 150^\circ\text{C}$	16.8		mJ
$t_{d(off)}$	$di/dt_{on} = 4100\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$	414		ns
$t_f$	$di/dt_{off} = 2500\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$	52		ns
$E_{off}$	$V_{GE} = +15/-15\text{ V}$	$T_j = 150^\circ\text{C}$	16.3		mJ
$R_{th(j-s)}$	per IGBT, $\lambda_{paste} = 0.8\text{ W}/(\text{Km})$		0.25		K/W

# SKiiP26GB12F4V1



MiniSKiiP® 2 Dual

## SKiiP26GB12F4V1


### Features

- Fast Trench 4 IGBTs
- Robust and soft freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognised: File no. E63532
- NTC T-Sensor

### Remarks

- Max. case temperature limited to  $T_C = 125^\circ\text{C}$
- Product reliability results valid for  $T_j \leq 150^\circ\text{C}$  (recommended)  
 $T_{j,op} = -40 \dots +150^\circ\text{C}$

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
<b>Inverse - Diode</b>						
$V_F = V_{EC}$	$I_F = 200\text{ A}$ $V_{GE} = 0\text{ V}$ chiplevel	$T_j = 25^\circ\text{C}$		2.20	2.52	V
		$T_j = 150^\circ\text{C}$		2.15	2.47	V
$V_{F0}$	chiplevel	$T_j = 25^\circ\text{C}$		1.30	1.50	V
		$T_j = 150^\circ\text{C}$		0.90	1.10	V
$r_F$	chiplevel	$T_j = 25^\circ\text{C}$		4.5	5.1	m $\Omega$
		$T_j = 150^\circ\text{C}$		6.3	6.9	m $\Omega$
$I_{RRM}$	$I_F = 200\text{ A}$	$T_j = 150^\circ\text{C}$		189		A
$Q_{rr}$	$di/dt_{off} = 3840\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		28.7		$\mu\text{C}$
$E_{rr}$	$V_{GE} = -15\text{ V}$ $V_{CC} = 600\text{ V}$	$T_j = 150^\circ\text{C}$		11.7		mJ
$R_{th(j-s)}$	per Diode, $\lambda_{paste} = 0.8\text{ W}/(\text{K}\cdot\text{m})$			0.34		K/W
<b>Module</b>						
$L_{CE}$				20		nH
$M_s$	to heat sink		2		2.5	Nm
$w$				50		g
<b>Temperature Sensor</b>						
$R_{100}$	$T_c = 100^\circ\text{C}$ ( $R_{25} = 5\text{ k}\Omega$ )			$493 \pm 5\%$		$\Omega$
$B_{25/85}$	$R(T) = R_{25} \cdot \exp[B_{25/85} \cdot (1/T - 1/298)]$ , [T]=K			3420		K



GB




Fig. 1: Typ. output characteristic, inclusive  $R_{CC'+EE'}$




Fig. 2: Rated current vs. temperature  $I_C = f(T_S)$




Fig. 3: Typ. turn-on /-off energy =  $f(I_C)$




Fig. 4: Typ. turn-on /-off energy =  $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs.  $I_C$




Fig. 8: Typ. switching times vs. gate resistor  $R_G$




Fig. 9: Transient thermal impedance of IGBT and Diode




Fig. 10: Typ. CAL diode forward charact., incl.  $R_{CC+EE}$




Fig. 11: Typ. CAL diode peak reverse recovery current





Fig. 12: Typ. CAL diode recovery charge


# SKiIP26GB12F4V1





For mounting please follow the assembly instruction

requirement for PCB Design:  
The MiniSKiIP area shall be covered with a maximum of circuit paths. This ensures a uniform area pressure


measure: mm  
tolerance: +/- 0,2



X (5 : 1)  
min. PCB pad size



standard pressure part  
pressure part is no part of MiniSKiIP Dual and must be ordered separately




Accessible for mounting of SMD (max. height 3.5) on PCB by customer. Except pressure areas and blocked areas!

requirement for PCB design:  
The pressure pin areas and more than 80% of the pressure edge areas must be on the same level and covered with circuit path. This ensures a uniform area pressure.

measure: mm  
tolerance: +/- 0,2

## pinout, dimensions



- ⊙ power connector
- control connector

## pinout

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

## **\*IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.